

Muttere 6kt.Klasse 8 - VF



Lagerprogram:	Høyde	Nøkkelvidde	Gjengestigning
Mutter M6 ISO 4032-8 VF	5,2	10	1,0
Mutter M8 ISO 4032-8 VF	6,8	13	1,25
Mutter M10 ISO 4032-8 VF	8,4	16	1,5
Mutter M12 ISO 4032-8 VF	10,8	18	1,75
Mutter M14 ISO 4032-8 VF	12,8	21	2,0
Mutter M16 ISO 4032-8 VF	14,8	24	2,0
Mutter M18 ISO 4032-8 VF	15,8	27	2,5
Mutter M20 +3/10 ISO 4032-8 VF	18	30	2,5
Mutter M20 ISO 4032-8 VF	18	30	2,5
Mutter M22 ISO 4032-8 VF	19,4	34	2,5
Mutter M24 ISO 4032-8 VF	21,5	36	3,0
Mutter M27 ISO 4032-8 VF	23,8	41	3,0
Mutter M30 ISO 4032-8 VF	25,6	46	3,5
Mutter M33 ISO 4032-8 VF	28,7	50	3,5
Mutter M36 ISO 4032-8 VF	31	55	4,0
Mutter M39 ISO 4032-8 VF	33,4	66	4,0
Mutter M42 ISO 4032-8 VF	34	65	4,5
Mutter M45 ISO 4032-8 VF	36	70	4,5
Mutter M48 ISO 4032-8 VF	38	75	5,0
Mutter M52 ISO 4032-8 VF	42	80	5,0
Mutter M56 ISO 4032-8 VF	45	85	5,5
Mutter M60 ISO 4032-8 VF	48	90	6,0
Mutter M64 ISO 4032-8 VF	51	95	6,0
Mutter M72 DIN 934-8 VF	58	105	6,0
Mutter M80 DIN 934-8 VF	64	115	6,0
Mutter M90 DIN 934-8 VF	72	130	6,0

Teknisk informasjon:

Mutterne er varmforsinket iht ISO 1461 tabell 4

Vi kan tilby 3.1 sertifikater og i tillegg dokumentasjon på tredjeparts test iht ISO 898-1:2009 for noen av dimensjonene. Klasse 8 er for bolter og gjengestenger i 8.8 stål.

For andre dimensjoner, gjenger eller overflatebehandlinger enn de som er listet opp – send oss en forespørsel på epost så tar vi kontakt med deg.

Nut hexagonal Grade 8 - HDG



Stock programme:	Height	Wrench size	Thread pitch
Nut M6 ISO 4032-8 HDG	5,2	10	1,0
Nut M8 ISO 4032-8 HDG	6,8	13	1,25
Nut M10 ISO 4032-8 HDG	8,4	16	1,5
Nut M12 ISO 4032-8 HDG	10,8	18	1,75
Nut M14 ISO 4032-8 HDG	12,8	21	2,0
Nut M16 ISO 4032-8 HDG	14,8	24	2,0
Nut M18 ISO 4032-8 HDG	15,8	27	2,5
Nut M20 +3/10 ISO 4032-8 HDG	18	30	2,5
Nut M20 ISO 4032-8 HDG	18	30	2,5
Nut M22 ISO 4032-8 HDG	19,4	34	2,5
Nut M24 ISO 4032-8 HDG	21,5	36	3,0
Nut M27 ISO 4032-8 HDG	23,8	41	3,0
Nut M30 ISO 4032-8 HDG	25,6	46	3,5
Nut M33 ISO 4032-8 HDG	28,7	50	3,5
Nut M36 ISO 4032-8 HDG	31	55	4,0
Nut M39 ISO 4032-8 HDG	33,4	66	4,0
Nut M42 ISO 4032-8 HDG	34	65	4,5
Nut M45 ISO 4032-8 HDG	36	70	4,5
Nut M48 ISO 4032-8 HDG	38	75	5,0
Nut M52 ISO 4032-8 HDG	42	80	5,0
Nut M56 ISO 4032-8 HDG	45	85	5,5
Nut M60 ISO 4032-8 HDG	48	90	6,0
Nut M64 ISO 4032-8 HDG	51	95	6,0
Nut M72 DIN 934-8 HDG	58	105	6,0
Nut M80 DIN 934-8 HDG	64	115	6,0
Nut M90 DIN 934-8 HDG	72	130	6,0

Technical information:

The nuts are hot-dip galvanized according to ISO 1461 table 4

We can offer 3.1 certificates and in addition documentation of third party tests according to ISO 898-1: 2009 for some of the dimensions. Grade 8 is for bolts and threaded rods in 8.8 steel.

For other dimensions, threads or surface treatments than those listed - send us a request by email and we will contact you.