

Korrugerte rør



Korrugerte rør for utsparing. Rørene er lett bøybare. Ved innstøping bør plastlokk benyttes.

Lagerprogram:

Ø50x5000
 Ø60x5000
 Ø75x5000
 Ø100x5000

Andre dimensjoner tilbys på forespørsel. Kan også tilbys i kappede/fixe lengder.

Teknisk informasjon:

Spiralviklede rør iht. EN 523-524, CE merket

Godstykkelse: 0,26 – 0,4mm

Oppfyller kravene i CPR/Byggvaredirektivet/EU Direktivet 305/2011/EU

Rørene er ubehandlet.

Dimensjon (mm):	Vekt (kg/m)	Lengde/rack (m)
Ø50x0,3	0,555	1500
Ø60x0,3	0,666	1000
Ø75x0,4	1,110	750
Ø100x0,4	1,480	350

Tilbehør:

Plastlokk/endelokk pr. dimensjon.

Corrugated duct



Corrugated duct for recesses. Duct is very flexible. For embedment in concrete, a plastic cap for end protection should be used.

Stock programme:

\varnothing 50x5000
 \varnothing 60x5000
 \varnothing 75x5000
 \varnothing 100x5000

Other sizes available on request. Also available in cut/fixed lengths.

Technical information:

Spirally wound duct according to EN 523-524, CE marked.

Thickness: 0.3-0.4 mm

Meets the requirements of Construction Products Regulation (CPR)/EU Directive 305/2011/EU

The duct is untreated.

Dimension:	Weight: (kg/m)	Length / rack (m)
\varnothing 50x0,3	0.555	1500
\varnothing 60x0,3	0.666	1000
\varnothing 75x0,4	1.110	750
\varnothing 100x0,4	1.480	350

Accessories:

Plastic caps/end caps per size.